

From: [Wright, Jeff](#)
To: [Gary Moore/R6/USEPA/US@EPA](#)
Subject: RE: Delta Shipyards Treatability Tests
Date: 02/12/2013 03:15 PM

Gary.

Wanted to follow-up on your Delta Shipyard slurry wall question. I spoke with our guys in Houston and got the following info,

“Assuming that you’d need to go 40 ft. deep, the wall would be about 60,000 vertical sq. ft. A typical cost for conventional slurry wall is about \$8-10/VSF or about \$600k not including mobe, disposal of excess soil and a number of other details that could at least double this cost. Sheet piling is about \$25/VSF so about \$1.5M, plus mobe and other details (no soil disposal required). These are not construction estimates but should give you an idea of the ballpark (\$1-2M). “

David and I did ask if the estimate per VSF would hold true for a more shallow confining clay layer (i.e. 8 – 10 ft.). They responded by stating that “If you’re only talking about 10 ft. to the bottom of the water-bearing zone, you could do this with a lot smaller excavator but you’d still have to set up the slurry-mixing operations, The VSF may be somewhat more expensive but the mobilization could be less.

Hope this helps,



Jeff Wright, CHMM
Weston Solutions, Inc.

an employee-owned company

13702 Coursey Blvd.,
Bldg #7, STE A
Baton Rouge, LA 70817

(225) 297-5415 Direct
(225) 278-8406 Cell

Jeff.Wright@westonsolutions.com

From: Moore.Gary@epamail.epa.gov [mailto:Moore.Gary@epamail.epa.gov]
Sent: Thursday, January 31, 2013 2:47 PM
To: Wright, Jeff
Subject: Re: Delta Shipyards Treatability Tests

Jeff:

Does LDEQ have a soil to groundwater number(s)?

Could you also ask someone about vinyl/composite sheet piling and what would be the best to use to place around the site to allow for dewatering and preventing water entering the pits?



9522441

Thanks

Gary Moore
Federal On-Scene Coordinator
EPA Region 6
Cell: 214-789-1627
Work: 214-665-6609
email: moore.gary@epa.gov

From: "Wright, Jeff" <Jeff.Wright@WestonSolutions.com>
To: Gary Moore/R6/USEPA/US@EPA
Cc: "Bordelon, David" <David.Bordelon@WestonSolutions.com>
Date: 01/29/2013 05:04 PM
Subject: Delta Shipyards Treatability Tests

Gary -

I spoke with our Kemron representative yesterday. The primary question he had was the number of source material samples to be analyzed (e.g. will we submit each Pit sample for individual Treatability Analysis). I mentioned to him that the samples we have from the site are geoprobe core cuttings and would not contain the same amount of %moisture as the in situ material. He stated that they could manipulate the %moisture content during the Treatability Study. We would need to define what %moisture to run the tests.

Our other option would be to remobilize to the site with an extended-boom trackhoe and collect a representative sample from each pit. I would suggest that if we were to remob and collect new samples that they be submitted as individual Treatability Samples. If we decide to go with what we have, I would suggest combining all cutting together and then have the lab run the tests with the %moisture set at a couple different levels (maybe 40% and 60%, but I'll research a little more). The trackhoe method would certainly be less subjective and more indicative of real world conditions. I could put together cost estimate for procuring trackhoe services (1-day) if you're interested.

Regardless of which materials we decide to use, he only needs the actual number of source material samples to put together a cost proposal. We could request three, which would probably be the conservative way to go. Let me know what you think.

Jeff Wright, CHMM
Weston Solutions, Inc.
an employee-owned company
13702 Coursey Blvd.,
Bldg #7, STE A
Baton Rouge, LA 70817
(225) 297-5415 Direct
(225) 278-8406 Cell
Jeff.Wright@westonsolutions.com

CONFIDENTIALITY: This email and attachments may contain information which is confidential and proprietary. Disclosure or use of any such confidential or proprietary information without the written permission of Weston Solutions, Inc. is strictly prohibited. If you received this email in error, please notify the sender by return e-mail and delete this email from your system. Thank you.

***** ATTACHMENT NOT DELIVERED

This Email message contained an attachment named
image001.jpg
which may be a computer program. This attached computer
program could
contain a computer virus which could cause harm to EPA's
computers,
network, and data. The attachment has been deleted.

This was done to limit the distribution of computer viruses
introduced
into the EPA network. EPA is deleting all computer program
attachments
sent from the Internet into the agency via Email.

If the message sender is known and the attachment was
legitimate, you
should contact the sender and request that they rename the
file name
extension and resend the Email with the renamed attachment.
After
receiving the revised Email, containing the renamed
attachment, you can
rename the file extension to its correct name.

For further information, please contact the EPA Call Center at
(866) 411-4EPA (4372). The TDD number is (866) 489-4900.

***** ATTACHMENT NOT DELIVERED

CONFIDENTIALITY: This email and attachments may contain information which is confidential and proprietary. Disclosure or use of any such confidential or proprietary information without the written permission of Weston Solutions, Inc. is strictly prohibited. If you received this email in error, please notify the sender by return e-mail and delete this email from your system. Thank you.